



BIO BASED SPRAY SYSTEMS, LLC

2506 Fair Road - Sidney, OH 45365 - Phone: (888) 743-7319 - Fax: (937) 660-6875

Spray applicator systems from BioBased Spray Systems provides everything needed for your agency or county to begin applying **BIORESTOR® Asphalt Rejuvenator** yourself!

Computerized Spray System

Spray systems are powered by reliable Honda engines equipped with electric start. Mated to the Honda engines are ACE centrifugal pumps supplying on-demand pressure to the system. The electric start and battery used for the spray system supply 12v power to either model of sprayer- keeping these systems from needing to be hardwired to the unit. This allows for quick installation and removal of the units not removing a needed fleet vehicle from commission. Control cables ran to the cab can also easily be more permanently mounted if the spray system is going to be used for an extended amount of time but are temporarily strung along and ran into a window of the spraying vehicle.

Included in **ALL** kits are 1 ½ " hoses for hooking up the tote to the spray system, stainless steel mixer to agitate/mix concentrate and dilute product, (2) tote connectors with caps, both red spray tips for 0.02 spray rate and white tips for 0.03 rate on construction joints/rumble strips, transfer hose to dilute product (1:1), extra pump seal kit, tote return lid, and some additional ware part/pieces.

Computerized Spray System

- Spray system embraces an electronic flowmeter coupled with a Raven 450 computer console to apply the input application rate.
- Control module is coupled with a GPS system which simultaneously adjust the application rate as speed varies. (within ±1 mph of your desired speed) typically 4-6 mph
- 12.5 foot spray bar with 2 folding 2 foot wings allow for maximum square yard coverage and 8.5 foot traveling width when not in use. Also wings break away if any interferences were to occur while treating the pavement.
- 50 feet of hand wand for tight areas and touch up work

Advantages	Disadvantages
System can correct for slight deviations in speed (± 1 mph) which helps apply desired rate -minimizing over or under application	Programing initially is more in-depth
Control bank has 3 valves allowing for each wing and the center bar to be independently tuned on and off without capping off or inserting nozzles	More expensive than simple speed/pressure
In cab computer can be selected to display multiple functions such as: speed, rate, distance traveled, and gallons used/left in tank	

The computerized feature can easily pay for itself with consistent product application.

Included are Vericom V-Sense brake meters and software. This trusted company provides friction meters which allows for before and after friction measurements in order to assure your agency is opening a pavement back up safely.

Computerized Truck Mounted Spray System **\$ 17,200**
Vericom V-Sense Brake Meter/GPS test monitoring

*See additional sheet for more information

Plus Shipping

FREE Training Videos Provided!

Optional additional items include:

- Raven Precision CR7 GPS w/ 500S Smart Antenna **\$2760.00**
 - See additional sheet for more information
- Empty IBC/Tote for initial dilution **\$150.00**
- On-site training:
 - 4-5 hours of understanding mixing, splitting totes, circulation of product, speed app for electronic device, pressure, valves, hand sprayer, ect. Note: All shown in video.

Approx. \$500.00 per day

*******Pricing for Set up and Training are subject to vary with location*******







If there are any questions please feel free to contact BioBased Spray Systems LLC or your local **BIORESTOR®** dealer!



BioBased Spray Systems LLC

www.biorestor.com

2506 Fair Rd

Sidney, OH 45365

mike@asi-roads.com

Ph 888-743-7319

Mike: Cell 937-726-0831

Luke: (855)-818-8673